

*Changes for the Better*

for a greener tomorrow



## CO<sub>2</sub> 2-Dimensional Laser Processing Systems ML4020RX Series



# 4020RX

*2-Dimensional Laser Processing Systems*

**BREAKTHROUGH  
INNOVATION**



# RX-Series 4 x 2m sheetsize!!



# 4020RX


## Reliable Refined Revolution

### High Productivity

- Shorter piercing time by High peak pierce
- Improved processing stability by FAB control
- High speed processing of thin material by F-CUT

#### High peak pierce

In mild steel up to t25mm, controlling the oxidation reaction and optimizing beam quality realize small diameter piercing in a short time.




**[Processing shape]**  
Material/Thickness: SS400 t16mm  
Assist gas: Oxygen  
Processing time on 4020RX as compared to previous model which is taken as 100%.



#### FAB control

Mitsubishi's Original "FAB control" greatly improves processing stability.

**Beam Optimized Technology  
FABRICATION**  
MITSUBISHI original "control"





Material: Mild steel t16mm Processing time on 4020RX as compared to previous model which is taken as 100%.

\*Processing time when used with high peak pierce

#### F-CUT

High-speed communication of oscillator and control unit controls the beam ON/OFF without axis stop and reduces the processing time.




### Low operating cost

- Small gap processing reduces the assist gas consumption
- ECO mode function reduces the cost during standby
- New clean technology increases the lifetime of optical parts

#### Low assist gas cost


Small gap processing (Nitrogen cutting) reduces the operating cost by approx.30%.



Note: Running cost is calculated with unit price of electricity and gas in Japan. (Calculated as gas: 0.2yen/ℓ)


#### Low power consumption

ECO mode function reduces the power consumption during standby by up to 99%.



#### New clean technology

Enhanced clean technology extends the life of the PR mirror drastically.




\*1: Dirt limit value X of PR mirror differs depending on the processing contents, required specifications, etc.  
\*2: Time of t1 and t2 that reach to the dirt limit value of PR mirror differ depending on the deterioration condition of the oscillator parts.

### Easy to Use

- Easy nesting allows quick on-site response
- Double-cut function allows high quality processing of protected sheet metal
- Offcut Cutting function easily cut offcuts. High material yield rate is achieved


#### Easy nesting

Allows for rectangular nesting at the laser's NC control to meet urgent needs for additional parts.




#### Double-cut function

Allows high quality cutting of poor quality material and protected sheet metal, which often causes cutting defects, in tow runs.



#### Offcut Cutting

Easily cut offcuts into several pieces by using the Offcut Cutting screen.



#### Optional Features

	ML60XF	ML45CF-R
F127mm (F5") Lens Cartridge	Standard	○
F254mm (F10") Lens Cartridge	Standard	○
Oil Spray	Standard	Standard
High Peak Piercing	Standard	Standard
Magnetic Damage Reduction	Standard	Standard
Automatic nozzle changer	○	○
Barcode Reader	Standard	Standard

○: Available —: Not Available

#### Cutting capability

Resonator	Material	Assist gas	Thickness (mm)												
			0	2	4	6	8	10	12	14	16	18	20	22	24
ML60XF	Mild steel (SS400)	Oxygen	[Bar chart showing capability up to 30mm]												
	Stainless steel (SUS304)	Nitrogen	[Bar chart showing capability up to 24mm]												
	Aluminum alloy (A5052)	Air	[Bar chart showing capability up to 12mm]												
ML45CF-R	Mild steel (SS400)	Oxygen	[Bar chart showing capability up to 30mm]												
	Stainless steel (SUS304)	Nitrogen	[Bar chart showing capability up to 24mm]												
	Aluminum alloy (A5052)	Air	[Bar chart showing capability up to 12mm]												

\* The above are processing capabilities based on special conditions. The acceptance criteria are as stated in the specifications.  
\* The actual performance/quality may vary depending on the surface condition and deviation in the material composition even if materials are of the same specifications.  
\* Variations in processing performance/quality may occur depending on the part geometry.  
\* Regarding mild steel (SS400) with a thickness over t19mm, capacities listed in this catalog are based on LS material (steel plate for laser cutting) of Chubu Steel Plate Co., Ltd.  
※ Optional

## Processing Machine Specifications

Model name		ML4020RX-45CF-R	ML4020RX-60F	
Drive system		Flying optics (3-axis beam movement)		
Control system		X-Y-Z simultaneous 3-axes (Z-axis height control is also possible)		
Dimensions and Performance	Target workpiece dimensions (mm)		4,050 x 2,060	
	Max. workpiece weight		1650	
	Table Pass height		880	
	Stroke	X-axis (mm)	4,100	
		Y-axis (mm)	2,100	
		Z-axis (mm)	150	
	Speed	Rapid travel speed	XY-axis (m/min)	Max. 100
			Z-axis (m/min)	Max. 65
		Max. processing feed speed (m/min)		50
	Accuracy	Positioning accuracy	XY-axis (mm)	0.05/500
Z-axis (mm)			0.1/100	
Repetition accuracy (mm)		±0.01 (X, Y-axis)		
Processing head		Auto-focus preset		
Power consumption of entire system (kW)※		77	98	
Weight (kg)	Machine	Approx. 12,000		
	Pallet changer	Approx. 4,000		

※ including dust collector, controller, resonator, and cooling system, depending on the machining program.

## Resonator Specifications

Model name	ML45CF-R	ML60XF	
Excitation method	3-axis SD excitation cross flow resonator		
Laser output characteristics	Pulse peak output (W)	5,000	7,000
	Rated output (W)	4,500	6,000
	Beam mode	Lower order (TEM <sub>01</sub> *main component)	
	Power stability (%)	±1 or less during power control (relative to rated output)	
	Output power adjustable range (%)	0-100	
Laser gas composition	CO <sub>2</sub> :CO:N <sub>2</sub> :He=8:4:60:28		
Laser gas consumption (L/hr)	Approx. 3		
Weight (kg)	Approx. 2,200	Approx. 2,250	
Standard features	Beam shutter, Visible laser, High-speed power sensor		

## Control System Specifications


Model name	LC30BX
Display screen	15" TFT (touch panel)
Hard disk (GB)	20
Program input method	Screen creation, USB (ver. 2.0), Ethernet
Operation method	Memory operation, HD direct operation

## Cooling System Specifications

Model name	ML45CF-R	ML60XF
Applicable resonator	45CF-R	60XF
Cooling method	Air	
Exterior dimensions (mm)	2,000 × 1,500 × 2,055	
Weight (kg)	Approx. 1,040	Approx. 1,240

## Standard layout

### ML4020RX (Water-Cooled)



**MITSUBISHI  
ELECTRIC**

MITSUBISHI ELECTRIC EUROPE B.V.  
Mechatronics Machinery Division

Gothaer Str. 8 · 40880 Ratingen · Germany  
Tel.: +49-(0)2102-486 6120 · Fax: +49-(0)2102-486 7090  
[www.mitsubishi-laser.de](http://www.mitsubishi-laser.de)

\* Not all models are supported for all countries and regions.

\* Machine specifications differ according to the country and region, so please check with your dealer.

\* Processing data provided in this brochure is for reference only.

Mitsubishi Electric Corporation Nagoya Works is a factory certified for ISO14001 (standards for environmental management systems) and ISO9001 (standards for quality assurance management systems)



Revised publication, effective Jan. 2014.  
Specifications are subject to change without notice.