



ServoSteel
Pres Besleme Sistemleri

SRV-MA SERIES

**MECHANICAL
DECOILERS**

MEKANİK RULO AÇICILAR / MECHANICAL DECOILERS





YATAY RULO AÇICI

MEKANİK RULO AÇICILAR

Mekanik rulo açıcılarımız 500 kg ile 2500 kg arasında rulo taşıma kapasitesine sahiptir. Bir kol yardımı ile mekanik olarak göbekten vida milli sıkma ve boşaltma yapmaktadır. Maliyeti düşüktür ve küçük alan kaplar. Motorlu, pnömatik üst baskı kolu ve frenli seçeneklerimiz vardır.

500 kg - 2500 kg rulo sac taşıma
30 mm - 500 mm rulo sac genişlik kapasitesi

Standart Özellikler

- Hız kontrol ayar sistemi
- Fren balata sistemi
- Mandren bismeni ile rulo göbeği sıkma
- İki yöne açılabilme
- Opsiyonel özellikler (*)

MECHANICAL DECOILERS

Our mechanic decoilers have a roll carriage capacity in between 500 kg and 2.500 kg. They perform hub screw mechanical clamping and discharge by the help of an arm. Its cost is low and covers a small area. We have options including engine, pneumatic top depressor arm and breaks.

500 kg - 2500 kg steel roll carriage
30 mm - 500 mm steel roll width capacity

Standard Features

- Speed control adjustment system
- Brake lining system
- Tightening roll hub by plunger system
- Ability to open to both sides
- Optional features (*)

TEKNİK BİLGİLER - TECHNICAL DETAILS

Model Model	Rulo Ağırlığı Material Weight (kg)	Malzeme Genişliği Material Width (mm)	Rulo Dış Çapı Max. Coil Outside Diameter (mm)	Rulo İç Çapı Max. Coil Inside Diameter (mm)	Motor Engine	Fren Break	Üst Baskı Hold Down Arm
SRV-MA500A	500	30 - 300	1300	300 - 550	✓		Optional
SRV-MA500LA	500	30 - 300	1600	300 - 550	✓		✓
SRV-MA500F	500	30 - 300	1300	300 - 550		✓	✓
SRV-MA750A	750	30 - 300	1300	350 - 550	✓		Optional
SRV-MA750LA	750	30 - 300	1600	350 - 550	✓		✓
SRV-MA750F	750	30 - 300	1300	350 - 550		✓	✓
SRV-MA1500A	1500	30 - 400	1300	400 - 550	✓		Optional
SRV-MA1500LA	1500	30 - 400	1600	400 - 550	✓		✓
SRV-MA1500F	1500	30 - 400	1300	400 - 550		✓	✓
SRV-MA2500A	2500	30 - 500	1300	450 - 550	✓		Optional
SRV-MA2500LA	2500	30 - 500	1600	450 - 550	✓		✓
SRV-MA2500F	2500	30 - 500	1300	450 - 550		✓	✓



Servosteel
Pres Besleme Sistemleri

SRV-MA SERIES

**MECHANICAL
DECOILERS**

KONİK MANDREN RULO AÇICILAR / CONICAL PLUNGER DECOILERS



KONİK MANDREN RULO AÇICILAR

Konik mandren rulo açıcılarımız 3000 kg ile 4000 kg rulo taşıma kapasitesine sahiptir. Bir kol yardımı ile mekanik olarak konik mandren iç sıkma ve boşaltma yapmaktadır. 600 - 800 - 1000 mm rulo genişliğinde ve 5 mm ye kadar sac kalınlığında sağlıklı çalışmaktadır.

**3000 kg - 4000 kg rulo sac taşıma
600 mm - 1000 mm rulo sac genişlik kapasitesi**

Standart Özellikler

- Hız kontrol ayar sistemi
- Fren balata sistemi
- Manren sistemi ile rulo göbeği sıkma
- İki yöne açılabilme
- Rulo sac tutucu pnömatik üst baskı
- Opsiyonel özellikler (*)

CONICAL PLUNGER DECOILERS

Our conical plunger decoilers have a roll carriage capacity of 3.000 kg and 4.000 kg. They perform conical plunger internal mechanical clamping and discharge by the help of an arm. They operate very well with a roll width of 600 - 800 - 1000 mm and sheet thickness up to 5 mm.

**3.000 kg -4.000 kg steel roll carriage
600 mm -1.000 mm steel roll width capacity**

Standard Features

- Speed control adjustment system
- Brake lining system
- Tightening roll hub by plunger system
- Ability to open to both sides
- Steel roll holder pneumatic top press
- Optional features (*)

TEKNİK BİLGİLER - TECHNICAL DETAILS

Model Model	Rulo Ağırlığı Material Weight (kg)	Malzeme Genişliği Material Widht (mm)	Rulo Dış Çapı Max. Coil Outside Diameter (mm)	Rulo İç Çapı Max. Coil Inside Diameter (mm)	Adaptörlü With Adapter	Rulo İç Çap Sıkma Mandrel Expansion	Motor Engine	Fren Break	Üst Baskı Hold Down Arm
SRV-MA3000-PUB	3000	80 - 600	1600	450 - 560	630	Mekanik Mechanical	✓		✓
SRV-MAF3000-PUB	3000	80 - 600	1600	450 - 560	630	Mekanik Mechanical		✓	✓
SRV-MA3000-PUB	3000	80 - 800	1600	450 - 560	630	Mekanik Mechanical	✓		✓
SRV-MA4000-PUB	4000	80 - 800	1600	450 - 560	630	Mekanik Mechanical		✓	✓
SRV-MAF4000-PUB	4000	100 - 1000	1600	450 - 560	630	Mekanik Mechanical	✓		✓
SRV-MA4000-PUB	4000	100 - 1200	1600	450 - 560	630	Mekanik Mechanical		✓	✓



Servosteel
Pres Besleme Sistemleri

SRV-HA SERIES

**HYDRAULIC
DECOILERS**

HİDROLİK RULO AÇICILAR / HYDRAULIC DECOILERS



HİDROLİK RULO AÇICILAR

Hidrolik rulo açıcılarımız 6000 kg ile 20000 kg arasında rulo taşıma kapasitesine sahiptir. Rulo iç çap sıkma ve boşaltma sistemi hidroliktir. İsteğe bağlı olarak motorlu sistemle çalışan ve hız kontrol ünitesi standart olan yükleme arabaları da üretilmektedir.

**6000 kg - 20000 kg rulo sac taşıma
1600 mm ye kadar rulo sac genişlik kapasitesi**

Standart Özellikler

- Pnömatik üst baskı kolu
- Hız kontrol sistemi
- Lazer sensörlü loop kontrol sistemi
- İki yöne açılabilme
- Opsiyonel özellikler (*)

HYDRAULIC DECOILERS

Our hydraulic decoilers have a roll carriage capacity in between 6.000 kg and 20.000 kg. Roll internal diameter clamping and discharge system is hydraulic. Loading vehicles, which are operating with engine system and whose speed control unit is standard, are also being produced upon request.

**6000 kg - 20000 kg steel roll carriage
Steel roll width capacity up to 1600 mm**

Standard Features

- Pneumatic top press arm
- Speed control system
- Laser sensor loop control system
- Ability to open to both sides
- Optional features (*)

TEKNİK BİLGİLER - TECHNICAL DETAILS

Model Model	Rulo Ağırlığı Material Weight (kg)	Malzeme Genişliği Material Width (mm)	Rulo Dış Çapı Max. Coil Outside Diameter (mm)	Rulo İç Çapı Max. Coil Inside Diameter (mm)	Adaptörlü With Adapter	Rulo İç Çap Sıkma Mandrel Expansion	Motor Engine	Fren Break	Üst Baskı Hold Down Arm
SRV-HA6000-PUB	6000	80 - 600	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HAF6000-PUB	6000	80 - 800	1600	450 - 560	640	Hidrolik/Hydraulic		✓	✓
SRV-HA6000-PUB	6000	80 - 1000	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HA8000-PUB	8000	80 - 800	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HAF8000-PUB	8000	80 - 1000	1600	450 - 560	640	Hidrolik/Hydraulic		✓	✓
SRV-HA8000-PUB	8000	80 - 1200	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HA10000-PUB	10000	80 - 1000	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HAF10000-PUB	10000	80 - 1200	1600	450 - 560	640	Hidrolik/Hydraulic		✓	✓
SRV-HA10000-PUB	10000	80 - 1300	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HA12000-PUB	2500	80 - 800	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HA12000-PUB	2500	80 - 1300	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HA15000-PUB	2500	80 - 1500	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓
SRV-HA20000-PUB	2500	80 - 1600	1600	450 - 560	640	Hidrolik/Hydraulic	✓		✓